



THE BRAND YOU TRUST

TriloG Pro Series

# MODEL 4064

Direct Screw Drive  
Garage Door Opener

Battery Backup Capable

**Model 4064H-B  
includes the  
battery backup**



**INDUSTRY BEST**  
**140 VOLT**  
**★★★★ DC MOTOR**

**HEAVIER DOORS,  
LIFTED FASTER™**



## Highlights

- **Powerful, fast performance** – Patented direct screw drive rail combined with powerful 140 volt DC motor provides maximum power and an opening speed of 12.0" per second\* to quickly open even the heaviest doors.
- **Soft Start & Stop Control** – DC technology allows your door to begin and end its movement smoothly instead of abruptly whenever you operate it, creating less noise and less wear on the door.
- **Big Door Capable** – For use on residential sectional doors up to 14' high and one-piece doors up to 8' high.
- **Maintenance-Free Direct Drive System** – Self-lubricating screw drive rail requires no maintenance under normal operating conditions.
- **Dependability** – A Limited Lifetime Warranty<sup>†</sup> on the motor and screw drive rail shows how confident Genie is that your opener will perform when you need it to for years to come.
- **Power on Demand** – Refers to the ability of the opener to continually monitor the door's travel and deliver just the right amount of power for smooth and consistent movement.
- **GenieSense™ Monitoring** – Automatic force profiling and diagnostic technology improves safety by stopping operation when significant changes occur.

THE GENIE STORY: Genie has a rich history in developing garage door openers that feature reliability, strength, safety, security, and convenience. Since 1954, Genie has produced millions of openers that serve millions of satisfied homeowners every day of every year. Shouldn't you have one in your garage? Genie — The Brand You Trust.

\* +/- 0.5 inches per second. Speed will slow with one-piece doors.  
\*\* When compared to industry standard, 12V motors  
† Limited non-transferable warranty. See Programming, Operation & Maintenance Manual for details.

# MODEL 4064



Motion Detector Lighting

## Standard Equipment & Warranty

SAFETY BEAMS	WALL CONSOLE	3-BUTTON REMOTE	MOTOR*	SCREW DRIVE RAIL*	PARTS*	ACCESSORIES*
--------------	--------------	-----------------	--------	-------------------	--------	--------------

## Features & Benefits

### POWER & CONTROL

**DC Motor Smart Technology** – The 140 volt DC motor offers powerful performance. The DC motor also allows for Soft Start & Stop control so the door begins and ends its travel smoothly instead of abruptly. This helps create less noise and less wear and tear on your door.

**Screw Drive Design** – Patented screw drive rail offers incredibly strong lifting force that allows the opener to lift residential sectional doors up to 14' high! By eliminating the gearbox used on belt and chain models, the screw drive design increases reliability since fewer parts means less chance for potential breakdown.

**C-Channel Rail** – Strong rail design helps promote durability and safety. Also conceals the screw drive rod for better appearance.

**Speed** – Opening speed of 12.0 inches/second\* gets you on your way faster.

### SAFETY

**Safe-T-Beam® Non-Contact Reversing System** – When objects pass through the infrared beam, the garage door automatically stops closing and reverses open without having to make physical contact with the door.

### SECURITY

**Intellicode® Access Security System** – Genie's superior encryption technology prevents piracy of the radio signal that operates your door by always selecting a new code from billions of combinations each time the opener is operated.

**Sure-Lock™ Control** – Allows you to lock out remote controls and wireless keypad at any time for increased security – also known as a vacation lock.

### CONVENIENCE

**Motion Detector Lighting** – Turns lights on automatically when you enter the garage for superior convenience and security. Lights stay on for 4 minutes once you exit garage or no motion is detected.

**Smart Illumination** – Light bulbs are positioned toward inside of garage instead of toward door for light where it's needed most. Light stays on for 4 minutes once opener is activated for ample time to get into house. Opener features bright lighting with (2) bulb capability. Genie branded LED light bulbs recommended. (If incandescent bulbs used, 100 watt max). See Genie LED bulb this page for additional details.

**Auto Seek Dual Frequency** – The system automatically uses 315 or 390 MHz frequency produced by the remote or keypad to help ensure the opener responds regardless of nearby frequency interference, such as military base equipment.

**Pre-Programmed Remote** – Ready to use out-of-the-box with simple steps to change the programming if so desired.

**HomeLink® & Car2U® Compatible** – Works with current and ALL previous versions of HomeLink® or Car2U®. No additional external repeater kit or compatibility bridge needed.

**6' Power Cord (Model 4064H)** – For high ceiling applications.

**CALIFORNIA RESIDENTS** – This opener has the option to add battery backup. As required by SB-989, all newly installed openers must have battery backup as of 7/1/19. To order this opener with battery backup, refer to Model 4064H-B. If needed, visit [www.geniecompany.com](http://www.geniecompany.com) or ask your Genie dealer for details.

## Convenience Options

### Aladdin Connect®

Remotely monitor and control your garage door from almost anywhere with your smart device. Time-based features allow you to set door to automatically close and/or notify after a set length of time; as well as schedule a specific hour and minute to close the door and/or notify when it does. Also allows for multiple individual user accounts so you can provide virtual key access for your garage door to a friend, relative, or service person for a certain time, a range of time, or permanently.



Compatible with:



Use the Aladdin Connect app to control any combination of 20 different Genie Wi-Fi integrated garage door openers or standalone Aladdin Connect Door Control Modules.

### Genie® Garage Door Opener LED Bulb

Common LED and CFL bulbs can emit interference to limit the range of garage door remotes. Incandescent light bulbs, which are being phased out due to energy inefficiency, can have their lives shortened by vibration associated with opener operation. The Genie LED bulb solves these and other problems to ensure the garage door opener light doesn't leave your garage in the dark!



### Wireless Keypad

Easy-to-program keypad mounts outside your door to give you convenient code access to your garage, which is great when you are outside without the remote control. Back-lit keypad lets you easily see the numbers & control up to 3 openers. Uses Auto-Seek Dual Frequency (315/390 MHz). Choose a color for the flip-up cover that best complements your home. White is standard, other colors sold separately.



### Battery Backup

Add this option and if the power goes out, Genie battery backup power goes on so you don't have to manually open and close the garage door!



### Illuminator™ LED Remote

Perfect for homeowners on the go, this 2-button remote features a bright LED flashlight and comes with an 18" lanyard for carrying convenience. It can operate up to two Genie garage door openers with Intellicode®.



### Wireless Wall Console

An attractive wall console that's completely wireless for flexible placement in the garage. Enjoy the optional pulsing back-light as well as delay button that gives ample time (up to 30 seconds) to exit the garage before the door begins moving. The work light button can turn just the opener's light on at any time. Compatible with most Genie Intellicode® openers made since 2013.



YOUR GENIE PROFESSIONAL DEALER:

\* +/- 0.5 inches per second. Speed will slow with one-piece doors.

† Limited non-transferable warranty. See Operation & Maintenance manual for details.

