

Door Series				COMMERCIAL OPERATOR ROLLING STEEL DOOR CHART (SQ. FT.)																							
				Steel Non-Insulated						Steel Insulated			Counter Doors		Grilles		FireStar® 2" Slat ₄		FireStar® 3" Slat ₄				FireStar® 3" Slat Insulated ₄		Shutters	Sheet	
Model	HP/ Voltage	UL LISTED	Max. Door Weight (Lbs.)	16 GA.	18 GA.	20 GA.	22 GA.	24 GA.	26 GA.	18 GA.	20 GA.	22 GA.	Aluminum	STL/ SST	Aluminum	STL/ SST	20 GA.	22 GA.	16 Ga.	18 GA.	20 GA.	22 GA.	20 GA.	22 GA.	Aluminum	26 GA.	
GCL-U	24 V DC	YES	850	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	121	100	
GCL-GCX	1/2 HP	YES	500	N/A	N/A	144	144	144	144	N/A	N/A	N/A	126*	126*	142	108	82	94	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
GCL-MJ GCL-MH	1/2 HP	YES	580	144	169	196	225	235	235	81	93	97	N/A	N/A	400	196	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	256	
GCL-J GCL-H	1/2 HP	YES	998	297	333	333	416	476	476	238	238	274	126	126	350	240	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	256	
GCL-J GCL-H	3/4 HP	YES	1220	359	419	419	552	618	N/A	276	276	309	126	126	450	310	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
GCL-J GCL-H	1 HP	YES	1440	388	461	461	606	621	N/A	297	296	382	126	126	610	450	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
GCL-GH	1/2 HP	YES	1310	250	277	277	333	360	360	194	194	222	126	126	360	280	210	270	128	144	166	220	120	128	N/A	256	
GCL-GH	3/4 HP	YES	1450	283	350	350	442	494	N/A	232	232	283	126	126	490	350	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
GCL-GH	1 HP	YES	1650	318	420	420	548	636	N/A	244	244	303	N/A	N/A	580	380	320	355	176	188	246	272	160	180	N/A	N/A	
GCL-GH	3 HP	YES	3696	962	1035	1152	1152	1152	N/A	728	728	986	N/A	N/A	982	982	576	576	342	390	576	576	300	324	N/A	N/A	