



NOTES:

1. PLEASE VERIFY VOLTAGE, PHASE & MOUNTING.
2. ALL OPTIONAL ARE AT ADDED COST.
3. A CLEARANCE OF 6" SHOULD BE ALLOWED FOR ACCESS TO ELECTRIC BOX.
4. CONTROL VOLTAGE IS A NEC CLASS 2 CIRCUIT.
5. AVERAGE DOOR TRAVEL SPEED IS 8" PER SECOND.

ELECTRIC OPERATOR: GCL-H (STANDARD DUTY)

DOOR TYPE: ROLLING STEEL

MOUNTING TYPE: FRONT OF HOOD

PROJECT:

ARCHITECT:

CONTRACTOR:

DISTRIBUTOR:

PLANT:

DRAWN BY: _____ DATE: _____

APPROVED BY: _____ DATE: _____

DWG NO. _____ SHT ___ OF ___

ENG. CERT. NO. _____

ARCHITECT DOOR NUMBER	QTY	FACTORY ORDER NUMBER	MOUNT TYPE	VOLTS					PHASE		CONTROL STATION			
				FRONT OF HOOD	115	208	230	460	575	1 PHASE	3 PHASE	3 BTN	KEY SWITCH	EXT. FLUSH 3 BUTTON

112274.0001 REV. -

